

DentOut®


PAINTLESS DENT REPAIR



Slide Hammer



Tabs



Adhesive
Sticks



Release
Agent



FIG. A




FIG. B



FIG. C



FIG. D



FIG. E

-Instructions- Slide Hammer Kit

*This system is designed for use on OEM Factory Paint Finishes Only!
DentOut does not recommend using this system if your vehicle has been repainted.*

- Determine the appropriate adhesive stick for the weather you are in.
Red = Warm to Hot weather 75° - 90° F **Yellow** = Cool Weather 55° - 75° F
- Insert adhesive stick into glue gun and warm up for 10-15 minutes prior to use.
Caution: The hot melt adhesive can reach temperatures in excess of 300°F. Severe burns may occur if hot melt adhesive comes in contact with skin. The use of protective gloves are highly recommended.
- Clean the dent with supplied release agent using a paper towel or clean cloth. Then clean the surface of the tab with the supplied release agent. (**Caution: Release agent is flammable.**)
- Apply hot melt adhesive to the tab. (**See Fig. A**)
Caution: Be careful not to allow the adhesive to drip over the edges as severe burns can occur.
- Place the tab softly on the center of the dent and hold in place for 10 seconds. Allow to cure 2 to 3 minutes. (**DO NOT** push the tab firmly on the dent! The more adhesive between the tab and the dent the more strength it will have.) (**See Fig. B**)
Hint: Use a dry eraser marker and mark a small spot on the **center** of the dent. This will make it easier to place the tab on the **center** of the dent.
- Attach the slide hammer to the tab and gently drag the weight to the end of the shaft. Slowly increase the force of each blow until desired result is achieved. (**See Fig. C**)
- To remove the adhesive simply apply 1-2 drops of release agent to the adhesive and peel off. (**See Fig. D**)
- If a high spot has been created use a small hammer and the supplied finishing tool and lightly tap the high spot until it is level with the original surface. (**See Fig. E**)
- Repeat steps 3-8 until desired results have been achieved.



Glue Gun



Plastic Razor Blades



Finishing Tool